

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1.-21. (Cancelled).

22. (Currently Amended) The system for deodorizing air of claim 21 40, ~~wherein~~ the passive filter member is being of the same shape as the second filter element.

23. (Currently Amended) The system for deodorizing air of claim 22, ~~wherein~~ the passive filter member is being the same size as the second filter element.

24. (Currently Amended) The system for deodorizing air of claim 21 40, ~~wherein~~ each of the passive filter member and the second filter element comprising ~~comprises~~ a cartridge.

25. (Currently Amended) The system for deodorizing air of claim 24, ~~wherein~~ each cartridge comprising ~~comprises~~ a top portion and a bottom portion and is being provided with one or more air inlets in the top portion and one or more air outlets in the bottom portion.

26. (Currently Amended) The system for deodorizing air of claim 25, ~~wherein~~ the upper exterior portion of the air moving member comprising ~~comprises~~ a housing having ~~a top portion with~~ an air inlet therein, and the second filter element cartridge being positioned ~~sits~~ on the upper exterior top portion of the housing of the air moving member so that the one or more air outlets on the bottom portion of the second filter element cartridge are at least partially in alignment with the air inlet of the air moving member.

27. (Currently Amended) The system for deodorizing air of claim 21 40, ~~wherein~~ the air moving member comprises a fan and the sodium bicarbonate in each of the first filter member and the second filter member is being sufficiently pervious to air so that the fan can convey air through the respective filter member.

28. (Currently Amended) The system for deodorizing air of claim 21 40, ~~wherein~~ each of the passive filter member and the second filter element comprising ~~comprises~~ a container having at least two sides comprised of an air pervious material with the sodium bicarbonate positioned between the at least two sides of air pervious material.

29. (Currently Amended) The system for deodorizing air of claim 28, ~~wherein~~ each container comprising ~~comprises~~ a bag made of air pervious material with the sodium bicarbonate positioned therein.

30. (Currently Amended) The system for deodorizing air of claim 21 40, ~~wherein~~ the first filter medium and the second filter medium each further comprising ~~comprises~~ activated carbon.

31. (Currently Amended) The system for deodorizing air of claim 21 40, ~~wherein the air moving member has an open top portion exposed to an outside environment and providing a base for the second filter element and wherein the second filter element is positioned on top of the air moving member and is~~ the second filter element being held in place on the air moving member ~~thereon~~ by gravitational force and by surface topology of interfacing parts of the second filter element and the air moving member.

32. (Currently Amended) The system for deodorizing air of claim 31, ~~wherein~~ the interfacing parts of the second filter element and the air moving member having ~~have~~ complementary hemispherical shapes.

33. (Currently Amended) The system for deodorizing air of claim 31, ~~wherein~~ the second filter element is being removable from the air moving member by lifting the second filter element upwardly.

34. (Currently Amended) The system for deodorizing air of claim 31, ~~wherein~~ at least one of the second filter element and the passive filter member comprising ~~comprises~~ a scent substance adapted to be emitted into the atmosphere.

35. (Currently Amended) A method for deodorizing air in confined space, comprising the steps of:

(a) providing a passive filter member comprising a first filter element, the first filter element comprising a first filter medium which at least partially comprises sodium bicarbonate, ~~wherein~~ and the passive filter member is being adapted to remove malodor from air without the assistance of an air moving member;

(b) providing a forced air filter member having an air flow path from an air inlet to an air outlet, the forced air filter member comprising a second filter element and an air moving member, the second filter element comprising a second filter medium which at least partially comprises sodium bicarbonate, ~~wherein~~ the air moving member having a housing and being is adapted to move air along the air flow path and through at least a portion of the second filter

medium, and ~~wherein the detachable passive member is interchangeable with the second filter element in the forced air filter member~~ being positioned on an upper exterior portion of the housing and detachable from the air moving member, interfacing parts of the second filter element and the upper exterior portion of the housing having complimentary surface topography, and the passive filter member being interchangeable with the second filter element for positioning on the exterior portion of the housing;

(c) positioning the passive filter member inside a confined space;

(d) positioning the forced air filter member inside the confined space during the same period of time as the passive filter member is positioned within the confined space, but in a location that is independent from the position of the passive filter member; and

(e) neutralizing odor in the air of the confined space by allowing air to come into proximity with the first filter member and by drawing air toward the sodium bicarbonate in the second filter member.

36. (Currently Amended) The method for deodorizing air in confined space of claim 35, ~~wherein~~ the passive filter member is being of the same shape as the second filter element.

37. (Currently Amended) The method for deodorizing air in confined space of claim 36, ~~wherein~~ the passive filter member is being the same size as the second filter element.

38. (Currently Amended) The method for deodorizing air in confined space of claim 35, ~~wherein~~ the confined space is being inside a refrigerator.

39. (Currently Amended) The method for deodorizing air in confined space of claim 35, ~~wherein~~ the confined space ~~comprising~~ comprises a compartment separate from the remainder of the confined space, and the passive filter member is being positioned inside the compartment and the forced air filter is being positioned in a remaining portion of the confined space.

40. (Currently Amended) A system for deodorizing air, comprising:
a passive filter member comprising a first filter element, the first filter element comprising a first filter medium which at least partially comprises sodium bicarbonate, ~~wherein~~ and the passive filter member is being adapted to remove malodor from air without the assistance of an air moving member; and

a forced air filter member having an air flow path from an air inlet to an air outlet, the forced air filter member comprising a second filter element and an air moving member, the second filter element comprising a second filter medium which at least partially comprises sodium bicarbonate, ~~wherein~~ the air moving member ~~has~~ having a housing and is being adapted to move air along the air flow path and through at least a portion of the second filter medium, ~~and wherein the second filter element is adapted to sit~~ being positioned on an upper exterior portion of the housing ~~in operation of the forced air filter member~~ and is detachable from the air moving member, interfacing parts of the second filter element and the upper exterior portion of the housing having complimentary surface topography;

~~wherein~~ and the passive filter member is being interchangeable with the second filter element ~~to sit~~ for positioning on the exterior portion of the housing.

41. (Currently Amended) An apparatus for deodorizing air, comprising:

a forced air filter member having an air flow path from an air inlet to an air outlet, the forced air filter member comprising a filter element and an air moving member, the filter element comprising a filter medium which at least partially comprises sodium bicarbonate, ~~wherein~~ the air moving member ~~has~~ having a housing and is being adapted to move air along the air flow path and through at least a portion of the filter medium, ~~and wherein the filter element is adapted to sit~~ being positioned on an upper exterior portion of the housing ~~in operation of the forced air filter member~~ and is detachable from the air moving member, interfacing parts of the filter element and the upper exterior portion of the housing having complimentary surface topography.